

Interzone 954

With an extensive global track record spanning over 25 years, Interzone® 954 is a high solids two-component modified epoxy, ideal for protecting and maintaining steel structures in the most severe environments. Particularly suited to maintenance situations, Interzone 954 is designed to give long term abrasion and corrosion protection in a single coat application.

Approved to NORSOK M501
for decks, splash zones, and submerged areas

Direct to metal (DTM) application in a single coat system removes the need for primers, increases productivity and reduces applied cost

Interzone 954

Standard two-coat epoxy system

Steel protected
85+
Million m²
worldwide

Tolerance to damp surfaces during application

Suitable for exposure to tidal sea water after just 2 hours

Up to
55%
time saving

| | | |
|---------|---------|----------------|
| | Coat 1* | Surface Prep** |
| Coat 2* | Coat 1* | Surface Prep** |

* Coating times to dry hard
** Estimated surface preparation time using ultra high pressure water jetting on 100m² (1.076ft²) surface area. Time will vary based on equipment and surface condition.

Interzone 954 delivers long-term performance in environments that combine a high potential for mechanical damage, chemical attack, atmospheric corrosion and immersion conditions.

international-pc.com/products/interzone-954

© Registered trademark of AkzoNobel in one or more countries. © 2021 Akzo Nobel N.V.